



TDL110 | Transport Data Logger

Transparency for your Supply Chain

PART NO | 0 273 600 024 001

By being attached to the shipment and measuring and recording relevant parameters like temperature, humidity, tilt, and shock, the TDL makes the delivery process of goods visible and traceable. These measurements are then documented and visualized through a mobile application. Since the limits of each parameter can be individually configured, any transgression of these limits is traceable and clearly assignable to the stations throughout the entire supply chain.

MEASUREMENT PARAMETERS



Shock



Humidity



Temperature



Tilt

APPLICATION ADVANTAGES

- ▶ Creates transparency within the entire supply chain
- ▶ Simplified configuration and visualization via mobile application
- ▶ Battery with an outstandingly long lifetime resulting in less handling effort



DEVICE SPECIFICATION

- | | |
|-------------------------------|--|
| ▶ Dimension (L x W x H) | 101,8 mm x 91 mm x 25 mm |
| ▶ Weight | 100 g |
| ▶ Power supply | CR 123A Lithium Battery, 1400 mAh |
| ▶ Battery lifetime | 2 Years (10 min. measuring cycle, +25 °C) |
| ▶ Enclosure protection class | IP 54 |
| ▶ Electrical protection class | III |
| ▶ Measuring interval | 1 min ... 4 hours (selectable) |
| ▶ Memory capacity | 2 Years (15 min. measuring cycle, typical usage) |

OPERATING CONDITIONS

- | | |
|-------------------------------|--|
| ▶ Operating temperature range | -25 °C ... +80 °C |
| ▶ Storage temperature range | 0 °C ... +40 °C |
| ▶ Humidity range | 0 % rH ... 100 % rH (non condensing) |
| ▶ Shock / Acceleration range | ±8 g per axis
±13.8 g three-dimensional |

ACCURACY

- ▶ Temperature $\pm 0.5\text{ }^{\circ}\text{C}$ (0 °C ... +60 °C)
 $\pm 1\text{ }^{\circ}\text{C}$ (-25 °C ... +80 °C)
- ▶ Humidity $\pm 5\%$ rH typical
 $\pm 10\%$ rH maximum
(20 % rH ... 80 % rH at 25 °C)
- ▶ Shock / Acceleration $\pm 10\%$



BOSCH

Invented for life

RESOLUTION

- ▶ Temperature 0.5 °C
- ▶ Humidity 1% rH
- ▶ Shock / Acceleration 0.1 g

COMMUNICATION

- ▶ Bluetooth Low Energy
- ▶ Range up to 40 m (dependent on external influences)

USER INTERFACE

- ▶ App free smartphone application for configuration and data analysis
- ▶ Status LED indication of device status, battery level and communication

INCLUDED DELIVERIES

- ▶ Device & built-in battery
- ▶ Quick Start Guide

DELIVERY SCOPE

- ▶ Packaging unit consists of 10 devices

DIMENSIONAL DRAWING



Contact us:

Bosch Connected Devices and Solutions

Interest: sales@bosch-connectivity.com

Support: info@bosch-connectivity.com

Visit our website:

www.bosch-connectivity.com



DOWNLOAD THE TDL APP, NOW!



App Store



Play Store