

Electronic Components

CHARGED:

KEM

C1206C823F4HAC7800

Manufacturer Part Number:	C1206C823F4HAC7800		
Manufacturer/Brand:	KEMET		
Part of Description:	CAP CER 1206 82NF 16V ULTRA STAB		
Datasheets:	C1206C823F4HAC7800.pdf		
RoHs Status:	Rohs Lead free / Rohs		
Stock Condition:	Compliant New original, Stock Available.		
Ship From:	Hong Kong		
Shipment Way:	DHL/Fedex/TNT/UPS/EMS		

Specifications

YC

Image may be representation. See specs for product details.

Manufacturer KEMET Description CAP CER 1206 82NF 16V ULTRA STAB Category Capacitors > Ceramic Capacitors Part Status Require For Quote & Check Stock Voltage - Rated 16V Tolerance ±1% Thickness (Max) 0.071* (1.80mm) Temperature Coefficient X8R Size / Dimension 0.126* L x 0.063* W (3.20mm x 1.60mm) Series C Ratings - Packaging Tape & Reel (TR) Packaging 1206 (3216 Metric) Other Names C1205C823F4HACTU Operating Temperature -55*C ~ 150*C Mounting Type Surface Mount, MLCC Mounting Type Surface Mount, MLCC Mounting Type 10 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Free Status / RoHS Status Lead free / RoHS Compliant	ption Dry tatus	CAP CER 1206 82NF 16V ULTRA STAB				
Capacitors > Ceramic CapacitorsPart StatusRequire For Quote & Check StockVoltage - Rated16VTolerance±1%Thickness (Max)0.071" (1.80mm)Temperature CoefficientXBRSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1266C23F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMonting Type1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	pry tatus					
Part StatusRequire For Quote & Check StockVoltage - Rated16VTolerance±1%Trickness (Max)0.071" (1.80mm)Temperature CoefficientX8RSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMountage Standard Lead Time18 WeeksLead Spacing-	tatus	Capacitors > Ceramic Capacitors				
Voltage - Rated16VTolerance±1%Thickness (Max)0.071" (1.80mm)Temperature CoefficientX9RSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-		Capacitors > Ceramic Capacitors				
Tolerance±1%Tolerance0.071" (1.80mm)Temperature CoefficientX8RSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206 823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	a Datad					
Thickness (Max)0.071" (1.80mm)Temperature CoefficientX8RSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	e - Kaleu					
Temperature CoefficientX8RSize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	nce	±1%				
Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C323F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	iess (Max)	0.071" (1.80mm)				
SeriesCRatings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	erature Coefficient	X8R				
Ratings-PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)				
PackagingTape & Reel (TR)Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-		C				
Package / Case1206 (3216 Metric)Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	S	-				
Other NamesC1206C823F4HACTUOperating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	jing					
Operating Temperature-55°C ~ 150°CMounting TypeSurface Mount, MLCCMoisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	je / Case					
Mounting Type Surface Mount, MLCC Moisture Sensitivity Level (MSL) 1 (Unlimited) Manufacturer Standard Lead Time 18 Weeks Lead Spacing -	Names	C1206C823F4HACTU				
Moisture Sensitivity Level (MSL)1 (Unlimited)Manufacturer Standard Lead Time18 WeeksLead Spacing-	ting Temperature	-55°C ~ 150°C				
Manufacturer Standard Lead Time 18 Weeks Lead Spacing -	ing Type	Surface Mount, MLCC				
Lead Spacing -	re Sensitivity Level (MSL)	1 (Unlimited)				
	acturer Standard Lead Time	18 Weeks				
Lead Free Status / RoHS Status Lead free / RoHS Compliant	pacing	-				
	ree Status / RoHS Status	Lead free / RoHS Compliant				
Height - Seated (Max)	- Seated (Max)	-				
Features Low ESL, High Temperature	es	Low ESL, High Temperature				
Failure Rate -	Rate	-				
0.082µF ±1% 16V Ceramic Capacitor X8R 1206 (3216		0.082µF ±1% 16V Ceramic Capacitor X8R 1206 (3216				
Capacitance 0.082µF	e Description	0.082µF				
Applications General Purpose						

C1206C823F4HAC7800 Electronic Components is 100% New Original from YIC Distributor, Search C1206C823F4HAC7800 Datasheets, PDF, Inventory at Y-IC.com Online, Order C1206C823F4HAC7800 KEMET with Warrantied and Confidence. Ship by DHL/FedEx/TNT/UPS Express. Support Payment with Telegraphic Transfer(T/T) or PayPal. RFQ C1206C823F4HAC7800 Email: Info@Y-IC.com

You May Be Also Be interested

In: C1206C823F3JACAUTO KEMET CAP CER 0.082UF 25V U2J 1206	C1206C822M8HAC7800 KEMET CAP CER 1206 8.2NF 10V ULTRA STA	C1206C822M4HACAUTO KEMET CAP CER 1206 8.2NF 16V ULTRA STA	C1206C823F5JAC7800 KEMET CAP CER 0.082UF 50V U2J 1206
C1206C823F4JACAUTO KEMET CAP CER 0.082UF 16V U2J 1206	C1206C823F4HACAUTO KEMET CAP CER 1206 82NF 16V ULTRA STAB	C1206C823F5JACAUTO KEMET CAP CER 0.082UF 50V U2J 1206	C1206C823F3JAC7800 KEMET CAP CER 0.082UF 25V U2J 1206

Related Hot keyword

C1206C823F4HAC7800 KEMET	C1206C823F4HAC7800 Data Sheet	C1206C823F4HAC7800 Datasheets	C1206C823F4HAC7800 PDF	KEMET C1206C823F4HAC7800
C1206C823F4HAC7800 Electronic	C1206C823F4HAC7800 Components	C1206C823F4HAC7800 Distributor	C1206C823F4HAC7800 Image	C1206C823F4HAC7800 Part
C1206C823F4HAC7800 Price	C1206C823F4HAC7800 Manufacturer	C1206C823F4HAC7800 Picture	C1206C823F4HAC7800 Stock	C1206C823F4HAC7800 Inventory
C1206C823F4HAC7800 New	C1206C823F4HAC7800 Original	C1206C823F4HAC7800 Warranted	C1206C823F4HAC7800 RFQ	C1206C823F4HAC7800 Order Online

Contact us:Info@Y-IC.com

ADD:Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.

Copyright $\ensuremath{\textcircled{C}}$ 2019 YIC International Co., Limited