










 <p>Expertise Applied   Answers Delivered</p>	<h2>250S130DR</h2>
	<p><b>Manufacturer Part Number:</b> <a href="#">250S130DR</a></p> <hr/> <p><b>Manufacturer/Brand:</b> <a href="#">Hamlin / Littelfuse</a></p> <hr/> <p><b>Part of Description:</b> PTC RESET 250/60V SMD 130MA</p> <hr/> <p><b>Datasheets:</b>  <a href="#">250S130DR.pdf</a></p> <hr/> <p><b>RoHs Status:</b>  Lead free / RoHS Compliant</p> <hr/> <p><b>Stock Condition:</b> New original, 2500 pcs Stock Available.</p> <hr/> <p><b>Ship From:</b> Hong Kong</p> <hr/> <p><b>Shipment Way:</b> DHL/Fedex/TNT/UPS/EMS</p>
	
<p>Image may be representation. See specs for product details.</p>	

### Specifications

Part Number	<a href="#">250S130DR</a>
Manufacturer	<a href="#">Hamlin / Littelfuse</a>
Description	PTC RESET 250/60V SMD 130MA
Category	<a href="#">Circuit Protection</a> > <a href="#">PTC Resettable Fuses</a>
Part Status	2500 pcs Stock
Series	POLY-FUSE®, 250S
Operating Temperature	-40°C ~ 85°C
Approvals	cURus, TUV
Ratings	-
Mounting Type	Surface Mount
Size / Dimension	0.370" L x 0.291" W (9.40mm x 7.40mm)
Height - Seated (Max)	-
Type	Polymeric
Lead Spacing	-
Package / Case	2-SMD
Thickness (Max)	0.146" (3.70mm)
Voltage - Max	60V (250V Int)
Current - Max	3A
Current - Hold (Ih) (Max)	130mA
Current - Trip (It)	260mA
Time to Trip	4s
Resistance - Initial (Ri) (Min)	4 Ohm
Resistance - Post Trip (R1) (Max)	20 Ohm
Resistance - 25°C (Typ)	-
Packaging	Tape & Reel (TR)











250S130DR is New Original in Stock, Search 250S130DR Datasheets, PDF, Inventory at Y-IC.com Online, Order 250S130DR Hamlin / Littelfuse with warrantied and confidence. RFQ 250S130DR : [Info@Y-IC.com](mailto:Info@Y-IC.com)

### You May Be Also Be interested In:

 <p><b>250RX30100M18X31.5</b> Rubycon CAP ALUM RAD</p>	 <p><b>250S130VMR</b> Hamlin / Littelfuse PTC RESET 250/60V VRT SMD 130MA</p>	 <p><b>250S41W335KV4E</b> Johanson Dielectrics, Inc. CAP CER 3.3UF 25V X7R 1210</p>	 <p><b>250S130VDR</b> Hamlin / Littelfuse FUSE PTC RESET 1.3A 250/60V SMD</p>
 <p><b>250S130-RBDR</b> Hamlin / Littelfuse PTC RESET 250/60V SMD RB 130MA</p>	 <p><b>250S130-RADR</b> Hamlin / Littelfuse PTC RESET 250/60V SMD RA 130MA</p>	 <p><b>250S130-RCDR</b> Hamlin / Littelfuse PTC RESET 250/60V SMD RC 130MA</p>	 <p><b>250S41X106KV4E</b> Johanson Dielectrics, Inc. CAP CER 10UF 25V X5R 1210</p>

### Hot Parts

[More](#)

 12102U560FAT2A	 250-001-001-10E	 250-002/K065-000	 D 250-003/K010-1910/000-1800	 250-003/K030-5378/000-2900
 250-5700-146	 250-7001-879	 D 2500BL14M050E	 2500BL14M100T	 2500BP15M400E/BF2012-L2R5
 25010AN-SU27	 250250-4AA20-1	 2502CSXH	 2502ESXH	 25040N SI27
 D 2509911-0003	 250R05L470JV4T	 250R05L470JV4T	 250X14W153MV4T	 250X14W223MV4T
 250X15W104MV4E	 AD1959YRSRL	 AT24C16D-SSHM-T	 AT93C66-10SC-2.7	 BLM18BD222SN1D
 BTS5590G	 C1005X5R0J104M	 D C2012X6S1H105KT00HN	 CR6L-500	 EMA1201-50EB16GRR
 HFA140NT60C	 D ICP-S0.5TN	 IR2E47U6/EL	 LD035A471KAB2A	 MAP3204C
 MAX6457UKD0A+T	 MAX921CSA	 MBB02070C1543FCT00	 MIC6315-31D4UY	 NFZ18SM121SN10D
 PSKD142/12	 PTMB150E6	 SD253R12S20PV	 D SKKD132/12	 SN74LVCH162244AG-P
 SPX3940AT-L-5-0/TR	 TPIC1356TDBTRG4	 TPS75618KTTT	 V48C3V3M75BL	 VLS6045EX-1R5N

Contact us:[Info@Y-IC.com](mailto:Info@Y-IC.com)

ADD:Unit A5-B5 No.509, 5/F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, HongKong.

Copyright © 2019 YIC International Co., Limited